| Ref<br># | Hits  | Search Query                                       | DBs   | Default<br>Operator | Plurals | Time Stamp       |
|----------|-------|--|---|---------------------|---------|------------------|
| L1       | 75520 | "396".clas.  | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:49 |
| L2       | 24309 | "396".clas. and shutter                            | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:49 |
| L3       | 370   | "396".clas. and shutter with pattern               | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:49 |
| L4       | 34    | "396".clas. and shutter with pattern with element  | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:51 |
| L5       | 2250  | "396".clas. and shutter near4 element              | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:52 |
| L6       | 11    | "396".clas. and shutter near4 element with pattern | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:56 |
| L7       | 405   | 382/313.ccls.                                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:57 |
| L8       | 14    | 382/313.ccls. and shutter                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR                  | ON      | 2005/06/22 10:57 |

∭e-mail



Home | Login | Logout | Access Information | Alerts |

## Welcome United States Patent and Trademark Office

Search Results

**BROWSE** 

**SEARCH** 

**IEEE XPLORE GUIDE** 

| Results for "(((sh | utter) <in>metadata)<and>(camera<in>metadata))"</in></and></in> |
|--------------------|---|
|--------------------|---|

Your search matched 79 of 354 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order

| A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order. |  |   |  |   |  |  |  |
|--|--|---|--|---|--|--|--|
| View Ses   | sion History   |   |  |   |  |  |  |
| New Search » Key   |  |   | Modify Search  (((shutter) <in>metadata)<and>(camera<in>metadata))</in></and></in>   |   |  |  |  |
|  |  | (((shu  |  |   |  |  |  |
| IEEE JNL IEEE Journal or<br>Magazine   |  |   | ☐ Check to search only within this results set   |   |  |  |  |
|  |  | Display Format:   Citation C Citation & Abstract  |  |   |  |  |  |
| IEE JNL  | IEE Journal or<br>Magazine   |   |  |   |  |  |  |
| IEEE<br>CNF  | IEEE Conference<br>Proceeding  | Select  | Article Information  | Vlew: 1-25   <u>26-</u>   |  |  |  |
| IEE CNF  | IEE Conference<br>Proceeding   |   | <ol> <li>An open and shut case [computer graphics]</li> <li>Glassner, A.;</li> </ol>   |   |  |  |  |
| IEEE<br>STD  | IEEE Standard  |   | Computer Graphics and Applications, IEEE Volume 19, Issue 3, May-June 1999 Page(s):82 - 92   |   |  |  |  |
|  |  | •   | AbstractPlus   Full Text: PDF(8600 KB)   IEEE JNL  |   |  |  |  |
|  |  |   | Frame-rate displacement measurement system utilizing an ultra<br>an optical correlator   | a-high-speed shut   |  |  |  |
|  |  |   | Toyoda, H.; Kobayashi, Y.; Mukohzaka, N.; Yoshida, N.; Hara, T.; C<br>Instrumentation and Measurement, IEEE Transactions on<br>Volume 44, Issue 3, June 1995 Page(s):755 - 758                               | Ohno, T.;   |  |  |  |
|  |  |   | AbstractPlus   Full Text: PDF (340 KB) IEEE JNL  |   |  |  |  |
|  |  | 3. Single camera three-dimensional endoscope system usin Lester, G.A.; Watts, J.; Wilmington, D.; Science, Measurement and Technology, IEE Proceedings- Volume 145, Issue 2, March 1998 Page(s):49 - 51 |  | rroelectric liquid c  |  |  |  |
|  |  |   | AbstractPlus   Full Text: PDF(308 KB) IEE JNL  |   |  |  |  |
|  | high-speed shutter camera and parallel aligned nen<br>(PAL-SLMs)<br>Toyoda, H.; Kobayashi, Y.; Mukohzaka, N.; Yoshida, N<br>Instrumentation and Measurement Technology Confere |   | Toyoda, H.; Kobayashi, Y.; Mukohzaka, N.; Yoshida, N.; Hara, T.; C<br>Instrumentation and Measurement Technology Conference, 1994. I<br>10th Anniversary. Advanced Technologies in I & M., 1994 IEEE         | atic liquid crystal spatial ligh<br>Hara, T.; Ohno, T.;<br>nce, 1994. IMTC/94. Conference |  |  |  |
|  |  |   | AbstractPlus   Full Text: PDF(248 KB) IEEE CNF   |   |  |  |  |
|  |  |   | 5. Analysis for Improvement of simultaneity of shuttering in an ultito, Y.; Katoh, Y.; Kagata, M.; Tomioka, S.; Enoto, T.; Magnetics, IEEE Transactions on Volume 36, Issue 4, July 2000 Page(s):1774 - 1778 | tra high-speed fra  |  |  |  |
|  |  |   | AbstractPlus   References   Full Text: PDF(128 KB)   IEEE JNL  |   |  |  |  |
|  |  |   | 6. 3-dimensional personal computer system Iwasaki, K.; Karibe, I.; Nakai, K.; Ueno, A.; Consumer Electronics, IEEE Transactions on   |   |  |  |  |